## NSN 5950-01-256-5292

Pulse Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-256-5292

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.070 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 0.700 inches single mounting facility single center group                 |
| Impedance Rating In Ohms:   |
| 52.0 single component single primary                                      |
| Pulse Repetition Rate:  |
| 5.0 kilohertz single component  |
| Body Length:  |
| 1.290 inches  |
| Body Width:   |
| 1.200 inches  |
| Body Height:  |
| 1.120 inches  |
| Maximum Operating Temp:   |
| 130.0 degrees celsius   |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Plug-in single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Features Provided:  |
| Tinned wire leads   |
| Winding Operating Current:  |
| 1.4 amperes ac single component single secondary                          |
| Winding Operating Voltage:  |
| 707.00 ac pounds per hour wet single component single secondary           |
| Terminal Type And Quantity:   |
| 4 pin   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| 1059h0  |

A058b0