

View Online at <https://aerobasegroup.com/nsn/5950-01-256-8872>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

Between 2.630 inches and 2.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Overall Width:

Between 2.250 inches and 2.380 inches

Frequency Rating:

54.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Height:

Between 3.690 inches and 3.810 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

500.0 milliamperes ac single component single secondary

Winding Operating Voltage:

70.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0