NSN 5950-01-258-9693

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-258-9693

| Reliability Indicator: | |
|--|--|
| Not established | |
| Inductance Rating: | |
| 3.90 microhenries single component single winding | |
| Coil Form Type: | |
| Solid single component | |
| Core Construction: | |
| S0lid single component | |
| Body Length: | |
| Between 0.325 inches and 0.345 inches | |
| Overall Diameter: | |
| 0.136 inches | |
| Maximum Operating Temp: | |
| 105.0 degrees celsius | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Terminal single group | |
| Rating Method: | |
| Electrical single component single winding | |
| Features Provided: | |
| Tinned wire leads | |
| Winding Conductor Size: | |
| 0.02010 inches american wire gage single component single winding | 1 |
| Winding Operating Current: | |
| 436.0 milliamperes dc single component single winding | |
| Dc Resistance Rating In Ohms: | |
| 0.411 single component single winding | |
| Quality Factor: | |
| 42 single component single winding | |
| Special Features: | |
| Magnetically shielded core | |
| Test Data Document: | |
| 81349-mil-c-15305 specification (includes engineering type bulletins | brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and sir | nilar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that | at are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: | |
| 2 wire lead | |
| Specification Data: | |
| 96906-ms21400 government standard | |
| Shelf Life: | |
| N/a | |
| | |

- Unit Of Measure:
- ---

NSN 5950-01-258-9693

Radio Frequency Coil - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

