## NSN 5950-01-258-9714

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-258-9714

| Reliability Indicator:  |
|---|
| Not established   |
| Inductance Type:  |
| Fixed   |
| Inductance Rating:  |
| 6.00 henry single component single winding  |
| Frequency Rating:   |
| 1.0 kilohertz single component  |
| Body Length:  |
| 1.281 inches  |
| Body Width:   |
| 0.688 inches  |
| Body Height:  |
| 1.656 inches  |
| Distance Between Mounting Facility Centers:   |
| 0.875 inches single mounting facility single center group   |
| Winding Quantity:   |
| 1 single component  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 2 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Rating Method:  |
| Electrical single component single winding  |
| Thread Size:  |
| 0.112 inches single group   |
| Winding Operating Current:  |
| 9.0 milliamperes dc single component single winding   |
| Dc Resistance Rating In Ohms:   |
| 510.000 single component single winding   |
| Test Data Document:   |
| 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 2 tab, solder lug   |
| Specification Data:   |
| 81349-mil-t-27/205 government specification   |

N/a

Shelf Life:

## NSN 5950-01-258-9714

Reactor - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A058b0