NSN 5950-01-258-9717

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-258-9717

| Note established Inductance Type: Fixed Inductance Rating: 300.00 millihennies single component single winding Frequency Rating: 300.00 millihennies single component Body Length: 1.281 inches Body Length: 1.281 inches Body Wildth: 0.688 inches Body Height: 1.585 inches Body Hei | |
|--|---|
| inductance Type: Fixed | Reliability Indicator: |
| Fixed Inductance Rating: 30.00 millihennies single component single winding Frequency Rating: 3.0 kilohertz single component Body Length: 1.281 inches Body Width: 0.688 inches Body Width: 0.688 inches Body Height: 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility Centers: 0.876 inches single mounting facility Centers: 0.876 inches single mounting facility Centers: 0.8775 inches single mounting facility Centers: 0.8786 inches single mounting facility Centers: 0.8787 inches single group Winding Quantity: 1 single component Inclosure Type: 1 termetally seaded Mounting Facility Quantity: 2 single group Mounting Method: Electrical single group Winding Operating Current: 0.112 inches single group Winding Operating Current: 0.0.112 inches single component single winding Dr Resistance Rating in Ohms: 25.000 single component single winding Dr Resistance Rating in Ohms: 25.000 single component single winding Trest Data Document: 81349-mil+27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Scries Designator: Unc single group Terminal Type And Quantity: | Not established |
| inductance Rating: 300.00 millihenries single component single winding Frequency Rating: 300.00 millihenries single component Body Length: 1.281 inches Body Length: 1.281 inches Body Width: 3.688 inches Body Height: 1.656 inch | Inductance Type: |
| Solution willibranies single component single winding Frequency Rating: 3.0 kilohetz single component Body Length: 1.281 inches Body Width: 0.688 inches Body Width: 0.688 inches Body Height: 1.656 inches Maximum Operating Temp: 10.5 degrees calsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Fleetrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding De Resistance Rating in Ohms: 25.000 single component single winding Tests Data Document: 81.349-mill-127 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Fixed |
| Frequency Rating: 3.0 kilohettz single component Body Length: 1.281 inches Body Wildth: 0.888 inches Body Wildth: 0.888 inches Body Height: 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosur Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Acuity Quantity: 1 single single group Mounting Mothod: Electrical single component single winding Threadd hole single group Winding Operating Current: 40.0 milliamperes do single component single winding De Rasisance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil+27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Inductance Rating: |
| 3.0 kilohertz single component Body Length: 1.281 inches Body Width: 0.888 inches Body Height: 1.686 inches Body Height: 1.686 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Betility Quantity: 2 single group Rating Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes de single component single winding Do Resistance Rating In Ohms: 5.000 single component single winding Test Data Document: 81349-mil-1-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | 300.00 millihenries single component single winding |
| Body Length: 1.281 inches Body Width: 0.688 inches Body Height: 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.876 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Threaded hole single group Winding Operating Current: 0.112 inches single group Winding Operating Current: 0.00 single group Winding Operating Current: 0.100 Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average', '*, etc.). Thread Sries Designator: Unc single group Terminal Type And Quantity: | Frequency Rating: |
| 1.281 inches Body Width: 0.688 inches Body Helpht: 1.686 inches Maximum Operating Temp: 105.0 degrees celaius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding De Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil+-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Dosignator: Unc single group Terminal Type And Quantity: | 3.0 kilohertz single component |
| Body Width: 0.688 inches Body Height: 1.686 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding De Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mill-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formatic excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Dosignato: Unc single group Terminal Type And Quantity: | Body Length: |
| 0.688 inches Body Height: 1.686 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Text Data Document: 81349-mill-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formatic excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | 1.281 inches |
| Body Height: 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Body Width: |
| 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding De Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mill-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | 0.688 inches |
| Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Body Height: |
| 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group | 1.656 inches |
| Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes de single component single winding De Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil+27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Maximum Operating Temp: |
| 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0.0 milliamperes de single component single winding De Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | 105.0 degrees celsius |
| Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Distance Between Mounting Facility Centers: |
| 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | 0.875 inches single mounting facility single center group |
| Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Winding Quantity: |
| Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | 1 single component |
| Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Inclosure Type: |
| 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Hermetically sealed |
| Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Mounting Facility Quantity: |
| Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | 2 single group |
| Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Mounting Method: |
| Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Threaded hole single group |
| Thread Size: 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Rating Method: |
| 0.112 inches single group Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Electrical single component single winding |
| Winding Operating Current: 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Thread Size: |
| 40.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | 0.112 inches single group |
| Dc Resistance Rating In Ohms: 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Winding Operating Current: |
| 25.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | 40.0 milliamperes dc single component single winding |
| Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Dc Resistance Rating In Ohms: |
| 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | 25.000 single component single winding |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | Test Data Document: |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc single group Terminal Type And Quantity: | 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| Thread Series Designator: Unc single group Terminal Type And Quantity: | excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| Unc single group Terminal Type And Quantity: | and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: | |
| Terminal Type And Quantity: | Unc single group |
| | |
| 2 tab, solder lug | 2 tab, solder lug |

81349-mil-t-27/205 government specification

Specification Data:

NSN 5950-01-258-9717

Reactor - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0