NSN 5950-01-258-9719

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-258-9719

Note established Inductance Type: Fixed Inductance Rating: 22.00 henry single component single winding Frequency Rating: 1.0 kilohertz single component Body Length: 1.281 inches Body Wildth: 0.888 inches Body Height: 1.656 inches Maximum Operating Temp: 1.550 degrees colsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosur Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Quarties 1 single component single winding Thread Size: 1 single component single winding De Resistance Rating In Ohms: 1 single component single winding Thread Size: 1 single component single winding Thread Size: 1 single component single winding Thread Size: 1 single component single winding Thread Series Designator: 1 single single group Winding Operating Current: 1 stayle military specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 1 xculdes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator:	
inductance Type: Fixed Inductance Rating: 22.00 henry single component single winding Frequency Rating: 1.0 kilohettz single component Body Length: 1.281 inches Body Width: 0.688 inches Body Width: 0.688 inches Body Height: 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.975 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Rating Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Stee: 0.112 inches single group Winding Operating Current: 4.0 milliamperes de single component single winding Thread Stees 186.000 single component single winding Thread Stees component single component single winding Thread Stees 186.000 single component single winding Thread Stees component single component single winding Test Data Document: 81349-milt-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator:	Reliability Indicator:
Fixed Inductance Rating: 22.00 henry single component single winding Frequency Rating: 1.0k kilohertz single component Body Length: 1.281 inches Body Width: 0.688 inches Body Height: 1.686 inches Body Height: 1.685 inches Body Height: Body He	Not established
Inductance Rating: 22.00 henry single component single winding Frequency Rating: 1.0 kilohertz single component Body Length: 1.281 inches Body Width: 1.281 inches Body Width: 1.656 inches Body Height: 1.656 inches Maximum Operating Temp: 1.650 inches Maximum Operating Temp: 1.650 degrees aleisus Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Bethod: Electrical single component single winding Thread de hole single group Winding Operating Current: 4.0 milliamperes do single component single winding De Resistance Rating in Ohms: 1980.000 single component single winding The Rating Derivanting Limbers 1980.000 single component single winding The Rating Derivanting Limbers 1980.000 single component single winding Test Data Document: 81349-mill-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", "etc.). Thread Series Designator:	Inductance Type:
22.00 henry single component single winding Frequency Rating: 1.0 kilohetz single component Body Length: 1.281 inches Body Width: 0.888 inches Body Width: 0.888 inches Body Height: 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosur Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding De Resistance Rating in Ohms: 1960.000 single component single winding Test Data Document: 81349-mil+27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator:	Fixed
Frequency Rating: 1.0 kilohertz single component Body Length: 1.281 inches Body Width: 0.688 inches Body Height: 1.656 inches Maximum Operating Temp: 1.650 degrees calsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 5 single group Mounting Facility Quantity: 6 single group Mounting Method: 6 Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes de single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Tost Data Document: 2 excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Inductance Rating:
1.0 kilohertz single component Body Length: 1.281 inches Body Width: 0.688 inches Body Height: 1.656 inches Body Height: 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Botween Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Heility Quantity: 1 single semponent inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes de single component single winding Dc Resistance Rating in Ohms: 1960.000 single component single winding Test Data Document: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', "average", ", etc.). Thread Series Designator:	22.00 henry single component single winding
Body Length: 1.281 inches Body Width: 0.688 inches Body Helght: 1.686 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 181349-milt-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator:	Frequency Rating:
1.281 inches Body Width: 0.688 inches Body Height: 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Rating Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 4.0 milliamperes de single component single winding De Rating Linches single group Winding Operating Current: 4.0 milliamperes de single component single winding Test Data Document: 1860.000 single component single winding Test Data Document: 2 excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	1.0 kilohertz single component
Body Width: 0.688 inches Body Height: 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding De Resistance Rating in Ohms: 1960.000 single component single winding Test Data Document: 81349-milt-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator:	Body Length:
0.688 inches Body Height: 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Mounting Method: Electrical single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Text Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	1.281 inches
Body Height: 1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Mounting Method: Thread shole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil+27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator:	Body Width:
1.656 inches Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding The Rating Method: 1960.000 single component single winding The Rating Operating Current: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	0.688 inches
Maximum Operating Temp: 105.0 degrees celsius Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 1 single somponent single mounting facility single center group Wounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes de single component single winding Dc Resistance Rating In Ohms: 1950.000 single component single winding Test Data Document: 81349-mil+-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Body Height:
Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Facility Quantity: 2 single group Mounting Method: Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Do Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-1-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	1.656 inches
Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Maximum Operating Temp:
0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	105.0 degrees celsius
Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Distance Between Mounting Facility Centers:
1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	0.875 inches single mounting facility single center group
Inclosure Type: Hernetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Winding Quantity:
Hernetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	1 single component
Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Inclosure Type:
2 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Hermetically sealed
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Mounting Facility Quantity:
Thread Series Designator: Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	2 single group
Rating Method: Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Mounting Method:
Electrical single component single winding Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Threaded hole single group
Thread Size: 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Rating Method:
 0.112 inches single group Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: 	Electrical single component single winding
Winding Operating Current: 4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Thread Size:
4.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	0.112 inches single group
Dc Resistance Rating In Ohms: 1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Winding Operating Current:
1960.000 single component single winding Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	4.0 milliamperes dc single component single winding
Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Dc Resistance Rating In Ohms:
81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	1960.000 single component single winding
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Thread Series Designator:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unc single group	
one enigle group	Unc single group
Terminal Type And Quantity:	
	2 tab, solder lug
	2 tab, solder lug

81349-mil-t-27/205 government specification

Specification Data:

NSN 5950-01-258-9719

Reactor - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0