NSN 5950-01-258-9728

Reactor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-01-258-9728 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.125 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.125 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.128 inches single group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 150.00 henry single component all winding |
| Frequency Rating: |
| 60.0 hertz single component |
| Body Length: |
| 1.625 inches |
| Body Outside Diameter: |
| 1.312 inches |
| Winding Quantity: |
| 2 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Rating Method: |
| Electrical single component all winding |
| Dc Resistance Rating In Ohms: |
| 1430.000 single component all winding |
| Test Data Document: |
| 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 4 tab, solder lug |
| Specification Data: |
| 81349-mil-t-27/162 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Demilitarization:

NSN 5950-01-258-9728

Reactor - Page 2 of 2



Fiig:

A058b0