

View Online at <https://aerobasegroup.com/nsn/5950-01-259-3434>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.735 inches single mounting facility single center group and 2.765 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.735 inches single mounting facility single center group and 1.765 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

140.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

Between 3.125 inches and 3.250 inches

Body Width:

Between 2.125 inches and 2.250 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

7.0 amperes ac single component all secondary

Winding Power Rating:

70.0 volts-amperes single component all secondary

Winding Operating Voltage:

8.00 ac volts single component all secondary and 10.00 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0