

View Online at <https://aerobasegroup.com/nsn/5950-01-260-3839>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.120 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.620 inches single mounting facility single center group

**Frequency Rating:**

12.0 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

5.0 volt-ampere single component

**Body Length:**

3.563 inches

**Body Width:**

3.063 inches

**Body Height:**

2.500 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

4.5 amperes ac single component single primary

**Criticality Code Justification:**

Zzzy

**Winding Operating Voltage:**

5.00 ac volts single component single secondary

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo3790

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

4 standoff, threaded stud

**Reference Number Differentiating Characteristics:**

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0