

View Online at <https://aerobasegroup.com/nsn/5950-01-260-6482>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.090 inches single mounting facility single center group and 1.110 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.740 inches single mounting facility single center group and 0.760 inches single mounting facility single center group

**Inductance Type:**

Fixed

**Inductance Rating:**

1.60 millihenries single component 2nd winding and 2.40 millihenries single component 2nd winding

**Frequency Rating:**

50.0 kilohertz single component

**Body Length:**

Between 2.740 inches and 2.760 inches

**Body Width:**

Between 1.490 inches and 1.510 inches

**Body Height:**

Between 1.140 inches and 1.160 inches

**Maximum Operating Temp:**

155.0 degrees celsius

**Winding Quantity:**

3 single component

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Rating Method:**

Electrical single component all winding

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

25.0 amperes dc single component 3rd winding

**Dc Resistance Rating In Ohms:**

0.010 single component 2nd winding

**Test Data Document:**

04971-1000832 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0