

View Online at <https://aerobasegroup.com/nsn/5950-01-260-6482>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.090 inches single mounting facility single center group and 1.110 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.740 inches single mounting facility single center group and 0.760 inches single mounting facility single center group

Inductance Type:

Fixed

Inductance Rating:

1.60 millihenries single component 2nd winding and 2.40 millihenries single component 2nd winding

Frequency Rating:

50.0 kilohertz single component

Body Length:

Between 2.740 inches and 2.760 inches

Body Width:

Between 1.490 inches and 1.510 inches

Body Height:

Between 1.140 inches and 1.160 inches

Maximum Operating Temp:

155.0 degrees celsius

Winding Quantity:

3 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component all winding

Thread Size:

0.112 inches single group

Winding Operating Current:

25.0 amperes dc single component 3rd winding

Dc Resistance Rating In Ohms:

0.010 single component 2nd winding

Test Data Document:

04971-1000832 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0