

View Online at <https://aerobasegroup.com/nsn/5950-01-265-1660>

**Reliability Indicator:**

Not established

**Inductance Rating:**

400.00 microhenries single component single winding and 1.00 millihenries single component single winding

**Coil Form Type:**

Hollow single component

**Core Construction:**

Powdered single component

**Adjustment Device Drive Type:**

Slotted screw single component

**Body Length:**

0.952 inches

**Body Outside Diameter:**

0.400 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing single group

**Rating Method:**

Electrical single component single winding

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

94.0 milliamperes dc single component single winding

**Dc Resistance Rating In Ohms:**

17.000 single component single winding

**Quality Factor:**

50 single component single winding and 60 single component single winding

**Adjustment Method And Quantity:**

1 adjustable core single component

**Test Data Document:**

81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

2 pin

**Specification Data:**

96096-ms90546 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0