

View Online at <https://aerobasegroup.com/nsn/5950-01-267-3978>

**Reliability Indicator:**

Not established

**Impedance Rating In Ohms:**

40000.0 single component single secondary

**Frequency Rating:**

300.0 hertz single component and 75.0 kilohertz single component

**Maximum Transformer Power Rating:**

250.0 milliwatts single component

**Primary To Secondary Turn Ratio:**

1 to 1 single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

0.350 inches

**Overall Diameter:**

Between 0.490 inches and 0.510 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Mounting Bolt Circle Diameter:**

0.350 inches single mounting facility single center group

**End Application:**

4920-01-136-2857 test set, automatic

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Plug-in single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Features Provided:**

Tinned wire leads

**Winding Operating Current:**

700.0 microamperes dc single component single primary

**Terminal Type And Quantity:**

7 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0