## NSN 5950-01-267-5805

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-267-5805

**Reliability Indicator:** 

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.680 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

0.550 inches single mounting facility single center group

**Overall Width:** 

1.078 inches

**Mounting Hole Diameter:** 

0.116 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

**Maximum Transformer Power Rating:** 

2.0 volt-ampere single component

**Body Length:** 

0.870 inches

**Body Width:** 

0.740 inches

**Body Height:** 

0.780 inches

**Maximum Operating Temp:** 

130.0 degrees celsius

**Inclosure Type:** 

Fully enclosed

**Mounting Facility Quantity:** 

2 single group

**Mounting Method:** 

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

**Winding Operating Current:** 

250.0 milliamperes ac single component single secondary

**Winding Operating Voltage:** 

8.00 ac volts single component single secondary

**Test Data Document:** 

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

5 turret

**Specification Data:** 

81349-mil-t-27/338 government specification

## NSN 5950-01-267-5805

Power Transformer - Page 2 of 2



he		

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0