

View Online at <https://aerobasegroup.com/nsn/5950-01-268-5249>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Slot Width:

0.203 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

75.0 volt-ampere single component

Body Length:

4.000 inches

Body Width:

3.000 inches

Body Height:

2.688 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

652.0 milliamperes ac single component single secondary

Winding Operating Voltage:

230.00 ac volts single component all primary

Special Features:

Suffix rb means primary and secondary fusing

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0