

View Online at <https://aerobasegroup.com/nsn/5950-01-269-0907>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.900 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.556 inches single mounting facility single center group

Frequency Rating:

50.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.750 inches

Body Width:

2.180 inches

Body Height:

1.560 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component and 1 tertiary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

707.0 milliamperes ac single component 3rd secondary

Winding Power Rating:

413.66 volts-amperes single component 4th secondary

Winding Operating Voltage:

45.50 ac volts single component 3rd secondary

Special Features:

Each terminal on the fourth secondary is split for dual connection

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

20 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0