## NSN 5950-01-270-2059

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-270-2059

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.415 inches single mounting facility single center group and 3.445 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.735 inches single mounting facility single center group and 2.765 inches single mounting facility single center group

### **Mounting Hole Diameter:**

0.213 inches single group and 0.223 inches single group

### **Frequency Rating:**

48.0 hertz single component and 480.0 hertz single component

### Input-output Phase Relationship:

Single phase to single phase single component

### Winding Shielding Method:

Internal shield brought out to terminal single component

### **Body Length:**

3.500 inches

### **Body Width:**

Between 3.485 inches and 3.515 inches

### **Body Height:**

Between 4.115 inches and 4.145 inches

### **Maximum Operating Temp:**

105.0 degrees celsius

### Inclosure Type:

Partially enclosed, half shell

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Unthreaded hole single group

### **Winding Function And Quantity:**

2 primary single component and 3 secondary single component

### **Features Provided:**

Color coded lead

### **Winding Operating Current:**

25.0 milliamperes dc single component 1st secondary

### **Winding Operating Voltage:**

6.80 ac volts single component 3rd secondary

### **Terminal Type And Quantity:**

13 wire lead

### Shelf Life:

N/a

### **Unit Of Measure:**

--

# NSN 5950-01-270-2059

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0