

View Online at <https://aerobasegroup.com/nsn/5950-01-270-3565>

Reliability Indicator:

Not established

Overall Length:

3.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.812 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Overall Height:

3.000 inches

Overall Width:

3.250 inches

Mounting Slot Width:

0.203 inches single group

Frequency Rating:

60.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded single component

Maximum Operating Temp:

55.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

750.0 milliamperes ac single component single secondary

Winding Operating Voltage:

75.00 ac volts single component single secondary and 105.00 ac volts single component single secondary and 125.00 ac volts single component single secondary

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0