NSN 5950-01-270-7015

Radio Frequency Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-270-7015

Reliability Indicator:
Not established
Inductance Rating:
39.00 microhenries single component single winding
Coil Form Type:
Solid single component
Body Length:
0.430 inches
Body Outside Diameter:
0.172 inches
Maximum Operating Temp:
125.0 degrees celsius
End Application:
Receiver-transmitter
Inclosure Type:
Fully enclosed
Mounting Method:
Terminal single group
Rating Method:
Rating Method: Electrical single component single winding
Electrical single component single winding
Electrical single component single winding Winding Operating Current:
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.930 single component single winding
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.930 single component single winding Quality Factor:
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.930 single component single winding Quality Factor: 50 single component single winding
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.930 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity:
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.930 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.930 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life:
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.930 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.930 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.930 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:
Electrical single component single winding Winding Operating Current: 205.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.930 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: