

View Online at <https://aerobasegroup.com/nsn/5950-01-270-8650>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.192 inches single group

Frequency Rating:

47.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

5.125 inches

Body Width:

3.750 inches

Body Height:

3.625 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

8.2 amperes ac single component single secondary

Winding Power Rating:

57.4 volts-amperes single component single secondary

Winding Operating Voltage:

73.00 ac volts single component single primary and 105.00 ac volts single component single primary

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0