

View Online at <https://aerobasegroup.com/nsn/5950-01-271-4817>

Reliability Indicator:

Not established

Overall Length:

3.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches all mounting facilities all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches all mounting facilities all center groupings

Overall Height:

2.870 inches

Overall Width:

3.000 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta and delta-wye

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded stud 1st group

Winding Function And Quantity:

1 primary single component and 7 secondary single component

Thread Size:

0.164 inches 2nd group

Winding Operating Current:

730.0 milliamperes ac single component 4th secondary

Winding Power Rating:

52.22 volts-amperes single component 3rd secondary

Winding Operating Voltage:

30.00 ac volts single component 3rd secondary

Special Features:

1 primary winding; 7 secondary windings

Test Data Document:

15280-40-054808 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

26 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0