

View Online at <https://aerobasegroup.com/nsn/5950-01-271-4819>

Reliability Indicator:

Not established

Overall Length:

Between 3.437 inches and 3.562 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.609 inches single mounting facility single center group and 2.641 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group

Overall Height:

Between 5.000 inches and 5.313 inches

Overall Width:

Between 2.937 inches and 3.062 inches

Frequency Rating:

50.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

139.2 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core single component

Maximum Operating Temp:

130.0 degrees celsius

End Application:

4920-01-166-2425 interconnecting

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

2.32 amperes ac single component all secondary

Winding Power Rating:

69.6 volts-amperes single component all secondary

Winding Operating Voltage:

60.00 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0