

View Online at <https://aerobasegroup.com/nsn/5950-01-271-8170>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

9.980 inches single mounting facility single center group and 10.020 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

9.480 inches single mounting facility single center group and 9.520 inches single mounting facility single center group

Mounting Hole Diameter:

0.615 inches single group and 0.635 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Primary and secondary shielded and brought out to terminal single component

Body Length:

15.000 inches

Body Width:

11.000 inches

Body Height:

11.250 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

6 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

600.0 milliamperes ac single component 4th secondary

Winding Power Rating:

9.6 volts-amperes single component 4th secondary

Winding Operating Voltage:

80.00 ac volts single component 2nd secondary

Terminal Type And Quantity:

19 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0