# NSN 5950-01-272-4177

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-272-4177

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.490 inches single mounting facility single center group and 1.510 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.365 inches single mounting facility single center group and 1.385 inches single mounting facility single center group

### **Mounting Hole Diameter:**

0.137 inches single group and 0.157 inches single group

#### Frequency Rating:

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Body Length:**

Between 2.030 inches and 2.090 inches

#### **Body Width:**

Between 1.720 inches and 1.780 inches

#### **Body Height:**

Between 1.780 inches and 1.840 inches

#### **Inclosure Type:**

Hermetically sealed with oil

# **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Unthreaded hole single group

#### **Features Provided:**

Color coded lead

# **Winding Operating Current:**

5.0 amperes dc single component single primary

#### Winding Operating Voltage:

0.90 dc volts single component single secondary and 5.10 dc volts single component single secondary

# **Special Features:**

Primary rated but not included

#### **Test Data Document:**

10001-3021909 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### **Terminal Type And Quantity:**

2 wire lead

#### Shelf Life:

N/a

# **Unit Of Measure:**

## Demilitarization:

No

# NSN 5950-01-272-4177

Current Transformer - Page 2 of 2



Fiig:

A058b0