

View Online at <https://aerobasegroup.com/nsn/5950-01-272-8936>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Humidity resistant and salt spray resistant and vibration resistant

Inductance Type:

Fixed

Inductance Rating:

23.40 microhenries single component all winding and 27.30 microhenries single component all winding

Frequency Rating:

15.0 kilohertz single component

Body Length:

1.000 inches

Body Outside Diameter:

1.250 inches

Maximum Operating Temp:

130.0 degrees celsius

Winding Quantity:

2 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component all winding

Thread Size:

0.138 inches single group

Winding Operating Current:

25.0 amperes dc single component all winding

Dc Resistance Rating In Ohms:

0.0057 single component all winding

Test Data Document:

10001-2916252 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0