

View Online at <https://aerobasegroup.com/nsn/5950-01-272-8936>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Humidity resistant and salt spray resistant and vibration resistant

**Inductance Type:**

Fixed

**Inductance Rating:**

23.40 microhenries single component all winding and 27.30 microhenries single component all winding

**Frequency Rating:**

15.0 kilohertz single component

**Body Length:**

1.000 inches

**Body Outside Diameter:**

1.250 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Winding Quantity:**

2 single component

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

1 single group

**Mounting Method:**

Threaded hole single group

**Rating Method:**

Electrical single component all winding

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

25.0 amperes dc single component all winding

**Dc Resistance Rating In Ohms:**

0.0057 single component all winding

**Test Data Document:**

10001-2916252 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

4 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0