

View Online at <https://aerobasegroup.com/nsn/5950-01-273-0758>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility single center group

Frequency Rating:

30.0 kilohertz single component

Primary To Secondary Turn Ratio:

300 to 1 single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

1.000 inches

Body Width:

0.750 inches

Body Height:

0.870 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

12.8 amperes dc single component single primary

Dc Resistance Rating In Ohms:

48.000 single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Specification Data:

53711-5616493 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0