

View Online at <https://aerobasegroup.com/nsn/5950-01-273-0762>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.312 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

427.0 volt-ampere single component

Winding Shielding Method:

Internal shield brought out to terminal single component and internal shield grounded to inclosure single component

Body Length:

5.220 inches

Body Width:

4.470 inches

Body Height:

5.030 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

12.0 amperes ac single component 1st secondary

Winding Power Rating:

312.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

26.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

3 standoff, threaded stud and 5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0