

View Online at <https://aerobasegroup.com/nsn/5950-01-273-0762>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.062 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.312 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

427.0 volt-ampere single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component and internal shield grounded to inclosure single component

**Body Length:**

5.220 inches

**Body Width:**

4.470 inches

**Body Height:**

5.030 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

12.0 amperes ac single component 1st secondary

**Winding Power Rating:**

312.0 volts-amperes single component 1st secondary

**Winding Operating Voltage:**

26.00 ac volts single component 1st secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

3 standoff, threaded stud and 5 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0