NSN 5950-01-274-5202

Power Transformer - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5950-01-274-5202

Reliability Indicator: Not established Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Input-output Phase Relationship: Single phase to single phase single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Single phase to single phase single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
 primary single component and 3 secondary single component Winding Operating Current: amperes ac single component 3rd secondary Winding Power Rating: volts-amperes single component single primary Winding Operating Voltage: 50 ac volts single component 2nd secondary Terminal Type And Quantity: tab, solder lug Shelf Life: N/a Unit Of Measure:
Winding Operating Current: 5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
5.0 amperes ac single component 3rd secondary Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Winding Power Rating: 410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
410.0 volts-amperes single component single primary Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Winding Operating Voltage: 6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
6.50 ac volts single component 2nd secondary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:
10 tab, solder lug Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure:
N/a Unit Of Measure:
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0