

View Online at <https://aerobasegroup.com/nsn/5950-01-274-6416>

Reliability Indicator:

Not established

Overall Length:

Between 0.532 inches and 0.594 inches

Frequency Rating:

17.0 kilohertz single component and 23.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Overall Diameter:

Between 1.782 inches and 1.844 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 8 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

6.0 milliamperes ac single component single primary

Winding Operating Voltage:

36.76 ac volts single component single primary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

18 tab, solder lug

Specification Data:

81349-mil-t-27/291 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0