

View Online at <https://aerobasegroup.com/nsn/5950-01-274-6503>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.490 inches single mounting facility single center group and 1.510 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.990 inches single mounting facility single center group and 1.010 inches single mounting facility single center group

Frequency Rating:

20.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.020 inches

Body Width:

1.520 inches

Body Height:

1.330 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

8.0 amperes dc single component 1st secondary

Winding Power Rating:

8.4 volts-amperes single component 2nd secondary

Winding Operating Voltage:

5.00 dc volts single component 1st secondary

Special Features:

First secondary winding split into two terminals per lead; voltages and currents have been rectified

Test Data Document:

80063-a3033966 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0