

View Online at <https://aerobasegroup.com/nsn/5950-01-274-9190>

Reliability Indicator:

Not established

Overall Length:

10.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.300 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

8.100 inches single mounting facility single center group

Overall Height:

8.710 inches

Overall Width:

8.720 inches

Pulse Repetition Rate:

1250.0 hertz single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Captive nut single group

Winding Operating Current:

20.0 amperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

8.00 ac kilovolts single component single winding

Special Features:

Items are being coded as critical to insure source inspection will be performed at the point of manufacture, prior to material receipt by the us navy or other dod components. These items are piece parts or end items in support of vital military hardware necessary to sustain the successful mission of the ships, submarines, and shore stations of the us navy. Critical features including, but not limited to, dimensions, tolerances/clearances, electronic characteristics, and metallurgical properties will bespecified for government q ar (quality assurance representatives) to insure the highest possible degree of quality and reliability of these parts being delivered under navicp contracts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0