## NSN 5950-01-275-0798

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-275-0798
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Moisture resistant and oil resistant and vibration resistant
Turn Quantity:
6 single component single winding
Inductance Type:
Fixed
Inductance Rating:
1.60 microhenries single component single winding
Frequency Rating:
1.0 kilohertz single component
Body Length:
0.380 inches
Body Outside Diameter:
0.625 inches
Maximum Operating Temp:
105.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
1 single group
Mounting Method:
Threaded hole single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Features Provided:
Tinned wire leads
Thread Size:
0.112 inches single group
Winding Conductor Size:
0.02535 inches american wire gage single component single winding
Winding Operating Current:
1.0 amperes dc single component single winding
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
2 wire lead

N/a

Shelf Life:

## NSN 5950-01-275-0798

Reactor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0