NSN 5950-01-275-2028

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-275-2028

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant and moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.360 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.350 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield grounded to core and mounting single component

Body Length:

2.100 inches

Body Width:

1.720 inches

Body Height:

1.800 inches

Maximum Operating Temp:

90.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Features Provided:

Color coded lead and tinned wire leads

Thread Size:

0.112 inches single group

Winding Operating Voltage:

200.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 wire lead

NSN 5950-01-275-2028

Power Transformer - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0