## NSN 5950-01-275-2028

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-275-2028

Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant and moisture resistant
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.360 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.350 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Three phase to three phase single component
Transformer Winding Connection Type:
Delta-wye
Winding Shielding Method:
Internal shield grounded to core and mounting single component
Body Length:
2.100 inches
Body Width:
1.720 inches
Body Height:
1.800 inches
Maximum Operating Temp:
90.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Features Provided:
Color coded lead and tinned wire leads
Thread Size:
0.112 inches single group
Winding Operating Voltage:
200.00 ac volts single component single primary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
9 wire lead

## NSN 5950-01-275-2028

Power Transformer - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

