

View Online at <https://aerobasegroup.com/nsn/5950-01-275-5898>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

3.900 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.373 inches single mounting facility single center group and 2.378 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.873 inches single mounting facility single center group and 0.878 inches single mounting facility single center group

Overall Height:

1.950 inches

Overall Width:

2.710 inches

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta and wye-wye

Maximum Operating Temp:

145.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

386.0 milliamperes ac single component single primary

Winding Operating Voltage:

23.50 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0