NSN 5950-01-275-9352

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-275-9352

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and moisture resistant and vibration resistant

Overall Length:

1.020 inches

Overall Width:

1.020 inches

Frequency Rating:

47.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Height:

1.375 inches

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

0.734 inches single mounting facility single center group and 0.766 inches single mounting facility single center group

End Application:

Interface unit, hyx-58/tsec

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Features Provided:

Color coded lead and tinned wire leads

Thread Size:

0.112 inches single group

Winding Operating Current:

50.0 milliamperes ac single component single primary

Winding Operating Voltage:

115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 wire lead

NSN 5950-01-275-9352

Power Transformer - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0