NSN 5950-01-276-3704

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-276-3704

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.188 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.750 inches single mounting facility single center group |
| Frequency Rating: |
| 30.0 hertz single component and 90.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 6.0 volt-ampere single component |
| Body Length: |
| 2.625 inches |
| Body Width: |
| 2.188 inches |
| Body Height: |
| 1.750 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 32.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 5.00 ac volts single component single primary |
| Terminal Type And Quantity: |
| 4 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |