

View Online at <https://aerobasegroup.com/nsn/5950-01-278-8205>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.984 inches single mounting facility single center group and 3.015 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.421 inches single mounting facility single center group and 2.453 inches single mounting facility single center group

Frequency Rating:

5.0 kilohertz single component and 6.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 3.850 inches and 3.910 inches

Body Width:

Between 3.350 inches and 3.410 inches

Body Height:

Between 3.970 inches and 4.030 inches

Maximum Operating Temp:

130.0 degrees celsius

End Application:

4935-00-178-0833 test set, radar

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

3.5 amperes ac single component single secondary

Winding Power Rating:

441.0 volts-amperes single component single secondary

Winding Operating Voltage:

58.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

16 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0