NSN 5950-01-279-1066

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-279-1066

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

Frequency Rating:

5.0 kilohertz single component and 6.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 1.563 inches and 1.625 inches

Body Width:

Between 1.563 inches and 1.625 inches

Body Height:

Between 2.250 inches and 2.375 inches

Maximum Operating Temp:

130.0 degrees celsius

End Application:

4935-00-178-0833 test set, radar

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

5.0 amperes dc single component 1st secondary

Winding Operating Voltage:

12.20 ac volts single component 1st secondary

Special Features:

First secondary terminals split for dual connection

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

NSN 5950-01-279-1066

Power Transformer - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0