NSN 5950-01-280-5437

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-280-5437

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.350 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.438 inches single group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 0.5 kilovolt-ampere single component |
| Body Length: |
| 5.500 inches |
| Body Width: |
| 4.375 inches |
| Body Height: |
| 4.375 inches |
| Maximum Operating Temp: |
| 115.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 4.4 amperes ac single component single secondary |
| Winding Power Rating: |
| 0.5 kilovolt-amperes single component single secondary |
| Winding Operating Voltage: |
| 450.00 ac volts single component single primary |
| Terminal Type And Quantity: |
| 4 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-01-280-5437

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0