NSN 5950-01-281-8171

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-01-281-8171 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 6.720 inches single mounting facility single center group and 6.780 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.350 inches single mounting facility single center group and 2.410 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.438 inches single group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 500.0 volt-ampere single component |
| Body Length: |
| 5.500 inches |
| Body Width: |
| Between 4.689 inches and 4.811 inches |
| Body Height: |
| 6.375 inches |
| End Application: |
| Switch-board assembly |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 4.35 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 450.00 ac volts single component single primary |
| Terminal Type And Quantity: |
| 4 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No

NSN 5950-01-281-8171

Power Transformer - Page 2 of 2



Fiig:

A058b0