

View Online at <https://aerobasegroup.com/nsn/5950-01-282-0053>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Overall Length:

4.060 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Overall Height:

3.560 inches

Overall Width:

1.750 inches

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta-wye

Maximum Transformer Power Rating:

7.0 watts single component

Winding Shielding Method:

Core grounded and brought out to terminal single component

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

7.0 amperes dc single component 4th secondary

Winding Operating Voltage:

9.00 dc volts single component 4th secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

1 turret and 24 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0