

View Online at <https://aerobasegroup.com/nsn/5950-01-282-2000>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.377 inches single mounting facility single center group and 3.497 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.690 inches single mounting facility single center group and 2.810 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.125 inches

Body Width:

Between 3.377 inches and 3.497 inches

Body Height:

3.437 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 4 secondary single component

Winding Operating Current:

750.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

9.62 ac volts single component 1st secondary

Terminal Type And Quantity:

9 tab, solder lug and 4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0