NSN 5950-01-282-2000

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-282-2000
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.377 inches single mounting facility single center group and 3.497 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.690 inches single mounting facility single center group and 2.810 inches single mounting facility single center group
Frequency Rating:
50.0 hertz single component and 400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to core single component
Body Length:
4.125 inches
Body Width:
Between 3.377 inches and 3.497 inches
Body Height:
3.437 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
2 primary single component and 4 secondary single component
Winding Operating Current:
750.0 milliamperes dc single component 2nd secondary
Winding Operating Voltage:
9.62 ac volts single component 1st secondary
Terminal Type And Quantity:
9 tab, solder lug and 4 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

. ...

A058b0