NSN 5950-01-282-2487

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-282-2487

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 6.125 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 4.000 inches single mounting facility single center group **Mounting Slot Width:** 0.281 inches single group **Frequency Rating:** 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component **Maximum Transformer Power Rating:** 7.4 kilovolt-ampere single component **Body Length:** 6.875 inches **Body Width:** 4.875 inches **Body Height:** 7.563 inches **Maximum Operating Temp:** 155.0 degrees celsius Inclosure Type: Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 225.0 amperes ac single component single secondary Winding Operating Voltage: 16.00 ac volts single component single secondary **Precious Material And Location:** Terminal surfaces silver **Precious Material:** Silver **Terminal Type And Quantity:** 5 threaded stud Shelf Life: N/a

NSN 5950-01-282-2487

Current Transformer - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0

