NSN 5950-01-282-5494

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-01-282-5494 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.035 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.410 inches single mounting facility single center group |
| Overall Width: |
| 2.250 inches |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Transformer Winding Connection Type: |
| Wye-delta-wye |
| Body Length: |
| 2.035 inches |
| Body Height: |
| 1.400 inches |
| Maximum Operating Temp: |
| 71.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 245.0 milliamperes ac single component 2nd secondary |
| Winding Operating Voltage: |
| 187.00 ac pounds per hour dry single component single primary and 204.00 ac pounds per hour with retaining chain single component single |
| primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 10 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-01-282-5494

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0