

View Online at <https://aerobasegroup.com/nsn/5950-01-283-8071>

**Reliability Indicator:**

Not established

**Overall Length:**

Between 4.500 inches and 4.560 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.780 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.050 inches single mounting facility single center group

**Overall Width:**

Between 3.770 inches and 3.830 inches

**Mounting Hole Diameter:**

0.208 inches single group and 0.228 inches single group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and brought out to terminal single component

**Body Height:**

4.400 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 6 secondary single component

**Features Provided:**

Color coded lead

**Winding Operating Current:**

8.0 amperes ac single component 2nd secondary

**Winding Power Rating:**

95.1 volts-amperes single component 2nd secondary

**Winding Operating Voltage:**

24.95 ac volts single component 3rd secondary

**Special Features:**

1 primary winding; 6 secondary windings

**Test Data Document:**

73030-sv798894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

3 tab, solder lug and 12 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0