

View Online at <https://aerobasegroup.com/nsn/5950-01-283-8071>

Reliability Indicator:

Not established

Overall Length:

Between 4.500 inches and 4.560 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.780 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.050 inches single mounting facility single center group

Overall Width:

Between 3.770 inches and 3.830 inches

Mounting Hole Diameter:

0.208 inches single group and 0.228 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Height:

4.400 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Features Provided:

Color coded lead

Winding Operating Current:

8.0 amperes ac single component 2nd secondary

Winding Power Rating:

95.1 volts-amperes single component 2nd secondary

Winding Operating Voltage:

24.95 ac volts single component 3rd secondary

Special Features:

1 primary winding; 6 secondary windings

Test Data Document:

73030-sv798894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 tab, solder lug and 12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0